

## ABSTRACT

The invention pertains to a configuration for forming a ventilation aperture having a  
5 small cross section, whereby a sealing part is placed in a passageway and the ventilation aperture  
is formed between the sealing part and the inner wall of the passageway. In order to simplify  
manufacturing and, in particular, make possible the use of injection-molded plastic parts  
throughout, the invention suggests that the sealing part should have a cylindrical stopper that is  
made of an elastically deformable material and can be inserted into the passageway, and has in  
10 its surface shell at least one axially continuous, channel-like depression, the outside diameter of  
which, when in the unstressed state, is oversized in comparison with the inside diameter of the  
passageway.

10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100